

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
22 February 2001 (22.02.2001)

PCT

(10) International Publication Number
WO 01/13452 A1

- (51) International Patent Classification⁷: **H01M 8/06**, 8/22, 8/10, 8/12
- (21) International Application Number: PCT/AU00/00974
- (22) International Filing Date: 16 August 2000 (16.08.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PQ 2234 16 August 1999 (16.08.1999) AU
- (71) Applicant (for all designated States except US): **CERAMIC FUEL CELLS LIMITED** [AU/AU]; 170 Browns Road, Noble Park, VIC 3174 (AU).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **FOGER, Karl** [AT/AU]; 2 Macartney Avenue, Kew, VIC 3101 (AU). **AHMED, Khaliq** [AU/AU]; 27 Fairway Drive, Rowville, VIC 3178 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— With international search report.
— With amended claims.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FUEL CELL SYSTEM



(57) Abstract: A process for producing electricity in a fuel cell (14) which comprises reacting a higher carbon (C₃₊) hydrocarbon fuel with steam in a steam pre-reformer (10) at a temperature in the pre-reformer of no greater than 500 °C to produce a fuel stream including hydrogen and no less than about 20 % by volume methane measured on a wet basis, and supplying the fuel stream and an oxidant to a high temperature fuel cell (14) in which the methane is reformed and electricity is produced by reacting the fuel stream at an anode of the fuel cell and reacting the oxidant at a cathode of the fuel cell.